

Tee-Style "Zero Dead-Leg" Diaphragm Valves



Valves are produced to order in Diaphragm Valve sizes 1/2" - 2" and virtually any user specified Mainline Socket Tee size available. Tee-Style Valve material options include PVC, CPVC, or Low Extractable PVC.

Valve End Connection options include Spigot, Socket & Thread, or patented Special Reinforced (SR) Female Plastic Thread.

Diaphragm Options include EPDM, FKM, PTFE with bonded EPDM backing, or PTFE with bonded FKM backing.

Pressure Rating @ 73°F (23°C), Water
Valve Sizes 1/2" - 2" (20mm - 63mm)
235 psi with Elastomer Diaphragms
150 psi with PTFE Diaphragms

Maximum Service Temperature
PVC = 140°F (60°C)
CPVC = 200°F (93°C)
Temperature/Pressure De-ratings Apply

CONTACT SPEARS® FOR SELECTION ASSISTANCE & MSRP

Quick View Selection Chart

The following Base Part Numbers must be completed according to desired configuration size. Contact Spears® for the appropriate Tee size x Valve size code designations to replace the "xxx" in each.

Diaphragm Material	PVC Base Part Number			Pressure Rating @ 73°F (23°C)
	Spigot	Socket & Threaded	SR Threaded	
EPDM	2727ZD-xxx	2729ZD-xxx	2721ZD-xxxSR	1/2" - 2" 235 psi
FKM	2737ZD-xxx	2739ZD-xxx	2731ZD-xxxSR	
PTFE, EPDM Backing	2797TZD-xxx	2729TZD-xxx	2721TZD-xxxSR	1/2" - 2" 150 psi
PTFE FKM Backing	2797VTZD-xxx	2739VTZD-xxx	2731VTZD-xxxSR	

Diaphragm Material	CPVC Base Part Number			Pressure Rating @ 73°F (23°C)
	Spigot	Socket & Threaded	SR Threaded	
EPDM	2727ZD-xxxC	2729ZD-xxxC	2721ZD-xxxCSR	1/2" - 2" 235 psi
FKM	2737ZD-xxxC	2739ZD-xxxC	2731ZD-xxxCSR	
PTFE, EPDM Backing	2797TZD-xxxC	2729TZD-xxxC	2721TZD-xxxCSR	1/2" - 2" 150 psi
PTFE FKM Backing	2797VTZD-xxxC	2739VTZD-xxxC	2731VTZD-xxxCSR	

Diaphragm Material	Low Extractable PVC Base Part Number			Pressure Rating @ 73°F (23°C)
	Spigot	Socket & Threaded	SR Threaded	
EPDM	2727ZD-xxxBL	2729ZD-xxxBL	2721ZD-xxxSRBL	1/2" - 2" 235 psi
FKM	2737ZD-xxxBL	2739ZD-xxxBL	2731ZD-xxxSRBL	
PTFE, EPDM Backing	2797TZD-xxxBL	2729TZD-xxxBL	2721TZD-xxxSRBL	1/2" - 2" 150 psi
PTFE FKM Backing	2797VTZD-xxxBL	2739VTZD-xxxBL	2731VTZD-xxxSRBL	

Note: Low Extractable PVC Valves are typically used with elastomer backed PTFE Diaphragms to maintain purity in most applications. Tee-Style Zero Dead-Leg Diaphragm Valves are a non-stock configuration. All orders are non-cancelable, non-returnable.