



# Globe Valves



## PRODUCT

Contact Spears® for any Information not found.

Valves Product  
**Globe Valves**



Pressure Rating @ 73°F (23°C), Water  
150 psi

Maximum Service Temperature  
PVC = 140°F (60°C)  
CPVC = 200°F (93°C)

Temperature/Pressure De-ratings Apply

All Valves Assembled with Silicone-Free,  
Water Soluble Lubricant  
Suitable for Vacuum Service

Internal Repair Kit includes 1-Bonnet O-ring along with a factory assembled (required) internal component replacement unit consisting of Bonnet assembled with Stem/O-rings, Seat & Seal Carrier components. Install in valve using existing valve Bolts/Nuts/Washers, and Handle/Nut.

**PVC Internal Repair Kit**

Size	Buna-N	EPDM	FKM	Std Pk	Mstr Pk	Prod Code
2-1/2	GL-BRK-025 <b>236.01</b>	GL-ERK-025 <b>570.83</b>	GL-VRK-025 <b>634.91</b>	1	0	299
3	GL-BRK-030 <b>263.02</b>	GL-ERK-030 <b>632.47</b>	GL-VRK-030 <b>704.97</b>	1	0	299
4	GL-BRK-040 <b>308.60</b>	GL-ERK-040 <b>741.69</b>	GL-VRK-040 <b>815.46</b>	1	0	299
6	GL-BRK-060 <b>672.39</b>	GL-ERK-060 <b>1139.72</b>	GL-VRK-060 <b>1163.03</b>	1	0	299

**CPVC Internal Repair Kits**

Size	EPDM	FKM	Std Pk	Mstr Pk	Prod Code
2-1/2	GL-ERK-025C <b>803.81</b>	GL-VRK-025C <b>893.14</b>	1	0	299
3	GL-ERK-030C <b>919.53</b>	GL-VRK-030C <b>1009.77</b>	1	0	299
4	GL-ERK-040C <b>1042.65</b>	GL-VRK-040C <b>1147.46</b>	1	0	299
6	GL-ERK-060C <b>1489.21</b>	GL-VRK-060C <b>1638.72</b>	1	0	299

**PVC Flanged Ends**

Size	Buna-N	EPDM	FKM	Std Pk	Mstr Pk	Prod Code
2-1/2	6013-025 <b>709.45</b>	6023-025 <b>750.81</b>	6033-025 <b>808.84</b>	1	0	620
3	6013-030 <b>813.25</b>	6023-030 <b>849.27</b>	6033-030 <b>945.13</b>	1	0	620
4	6013-040 <b>922.62</b>	6023-040 <b>1102.95</b>	6033-040 <b>1211.93</b>	1	0	620
6	6013-060 <b>1418.93</b>	6023-060 <b>1696.69</b>	6033-060 <b>1730.51</b>	1	0	620

**CPVC Flanged Ends**

Size	EPDM	FKM	Std Pk	Mstr Pk	Prod Code
2-1/2	6023-025C <b>1138.36</b>	6033-025C <b>1195.56</b>	1	0	622
3	6023-030C <b>1195.00</b>	6033-030C <b>1328.44</b>	1	0	622
4	6023-040C <b>1552.03</b>	6033-040C <b>1706.12</b>	1	0	622
6	6023-060C <b>2416.58</b>	6033-060C <b>2437.01</b>	1	0	622