

Valves Product
Globe Valves



Pressure Rating @ 73°F (23°C), Water
 150 psi

Maximum Service Temperature
 PVC = 140°F (60°C)
 CPVC = 200°F (93°C)

Temperature/Pressure De-ratings Apply

All Valves Assembled with Silicone-Free,
 Water Soluble Lubricant
 Suitable for Vacuum Service

Internal Repair Kit includes 1-Bonnet O-ring along with a factory assembled (required) internal component replacement unit consisting of Bonnet assembled with Stem/O-rings, Seat & Seal Carrier components. Install in valve using existing valve Bolts/Nuts/Washers, and Handle/Nut.

PVC Internal Repair Kit

Size	Buna-N	EPDM	FKM	Std Pk	Mstr Pk	Prod Code
2-1/2	GL-BRK-025 224.21	GL-ERK-025 542.29	GL-VRK-025 603.16	1	0	299
3	GL-BRK-030 249.87	GL-ERK-030 600.85	GL-VRK-030 669.72	1	0	299
4	GL-BRK-040 293.17	GL-ERK-040 704.61	GL-VRK-040 774.69	1	0	299
6	GL-BRK-060 638.77	GL-ERK-060 1082.73	GL-VRK-060 1104.88	1	0	299

CPVC Internal Repair Kits

Size	EPDM	FKM	Std Pk	Mstr Pk	Prod Code
2-1/2	GL-ERK-025C 763.62	GL-VRK-025C 848.48	1	0	299
3	GL-ERK-030C 873.55	GL-VRK-030C 959.28	1	0	299
4	GL-ERK-040C 990.52	GL-VRK-040C 1090.09	1	0	299
6	GL-ERK-060C 1414.75	GL-VRK-060C 1556.78	1	0	299

PVC Flanged Ends

Size	Buna-N	EPDM	FKM	Std Pk	Mstr Pk	Prod Code
2-1/2	6013-025 673.98	6023-025 713.27	6033-025 768.40	1	0	620
3	6013-030 772.59	6023-030 806.81	6033-030 897.87	1	0	620
4	6013-040 876.49	6023-040 1047.80	6033-040 1151.33	1	0	620
6	6013-060 1347.98	6023-060 1611.86	6033-060 1643.98	1	0	620

CPVC Flanged Ends

Size	EPDM	FKM	Std Pk	Mstr Pk	Prod Code
2-1/2	6023-025C 1081.44	6033-025C 1135.78	1	0	622
3	6023-030C 1135.25	6033-030C 1262.02	1	0	622
4	6023-040C 1474.43	6033-040C 1620.81	1	0	622
6	6023-060C 2295.75	6033-060C 2315.16	1	0	622