

Valves Product Gate Valves



Gate Valves



**1/2" - 2"
Socket/Threaded Style**

2-1/2" - 3" Socket Style

4" Socket Style

Pressure Rating @ 73°F
(23°C), Water
1/2" - 2" 200 psi
2-1/2" - 3" 150 psi
4" 235 psi
Flanged 150 psi

Maximum Service Temperature
PVC = 140°F (60°C)
CPVC = 200°F (93°C)
Temperature/Pressure De-ratings Apply

CPVC Gate-Wedge on CPVC Valve
All Valves Assembled with Silicone-Free, Water Soluble Lubricant
See Gate Valve Accessories & Repair Kits Section for Additional Options and Features

PVC

Size	Buna-N	EPDM	FKM	Std Pk	Mstr Pk	Prod Code
------	--------	------	-----	--------	---------	-----------

Threaded Ends

1/2	2011-005 25.46	2021-005 27.95	2031-005 30.78	12	0	200
3/4	2011-007 31.14	2021-007 34.27	2031-007 36.07	12	0	200
1	2011-010 36.91	2021-010 40.64	2031-010 44.75	12	0	200
1-1/4	2011-012 51.03	2021-012 56.16	2031-012 61.74	6	0	200
1-1/2	2011-015 65.12	2021-015 72.35	2031-015 78.78	6	0	200
2	2011-020 83.63	2021-020 92.07	2031-020 101.22	6	0	200
2-1/2	2011-025 462.39	2021-025 508.62	2031-025 559.51	1	0	201

SR Threaded Ends

3	2011-030SR 462.39	2021-030SR 508.62	2031-030SR 559.51	1	0	201
4	2011-040SR 907.41	2021-040SR 1008.24	2031-040SR 1109.03	1	0	201

Socket Ends

1/2	2012-005 25.46	2022-005 27.95	2032-005 30.78	12	0	200
3/4	2012-007 31.14	2022-007 34.27	2032-007 36.07	12	0	200
1	2012-010 36.91	2022-010 40.64	2032-010 44.75	12	0	200

PVC (continued)

Size	Buna-N	EPDM	FKM	Std Pk	Mstr Pk	Prod Code
------	--------	------	-----	--------	---------	-----------

Socket Ends

1-1/4	2012-012 51.03	2022-012 56.16	2032-012 61.74	6	0	200
1-1/2	2012-015 65.12	2022-015 72.35	2032-015 78.78	6	0	200
2	2012-020 83.63	2022-020 92.07	2032-020 101.22	6	0	200
2-1/2	2012-025 462.39	2022-025 508.62	2032-025 559.51	1	0	201
3	2012-030 462.39	2022-030 508.62	2032-030 559.51	1	0	201
4	2012-040 907.41	2022-040 1008.24	2032-040 1109.03	1	0	201

Flanged Ends

1/2	2013-005 123.29	2023-005 139.81	2033-005 160.24	4	0	200
3/4	2013-007 138.73	2023-007 156.99	2033-007 179.12	4	0	200
1	2013-010 152.34	2023-010 172.08	2033-010 197.64	4	0	200
1-1/4	2013-012 171.59	2023-012 197.00	2033-012 233.80	3	0	200
1-1/2	2013-015 200.28	2023-015 228.62	2033-015 268.59	3	0	200
2	2013-020 257.80	2023-020 270.86	2033-020 289.97	2	0	200
2-1/2	2013-025 577.97	2023-025 773.86	2033-025 851.23	1	0	201
3	2013-030 577.97	2023-030 773.86	2033-030 851.23	1	0	201
4	2013-040 1137.66	2023-040 1264.14	2033-040 1390.55	1	0	201

CPVC

Size	Buna-N	EPDM	FKM	Std Pk	Mstr Pk	Prod Code
------	--------	------	-----	--------	---------	-----------

Threaded Ends

1/2	2011-005C 74.53	2021-005C 82.77	2031-005C 91.09	12	0	202
3/4	2011-007C 80.59	2021-007C 89.52	2031-007C 98.48	12	0	202
1	2011-010C 88.34	2021-010C 98.16	2031-010C 107.94	12	0	202
1-1/4	2011-012C 155.15	2021-012C 172.41	2031-012C 189.65	6	0	202
1-1/2	2011-015C 169.59	2021-015C 188.96	2031-015C 207.86	6	0	202
2	2011-020C 196.20	2021-020C 217.96	2031-020C 239.76	6	0	202
2-1/2	2011-025C 730.57	2021-025C 788.36	2031-025C 856.05	1	0	203

SR Threaded Ends

3	2011-030CSR 980.92	2021-030CSR 1089.61	2031-030CSR 1210.69	1	0	203
4	2011-040CSR 1765.62	2021-040CSR 1961.77	2031-040CSR 2179.75	1	0	203

Socket Ends

1/2	2012-005C 74.53	2022-005C 82.77	2032-005C 91.09	12	0	202
3/4	2012-007C 80.59	2022-007C 89.52	2032-007C 98.48	12	0	202



Valves Product
Gate Valves & Plug Gate Valves

Gate Valves

Plug Gate Valves

CPVC (continued)

Size	Buna-N	EPDM	FKM	Std Pk	Mstr Pk	Prod Code
Socket Ends						
1	2012-010C 88.34	2022-010C 98.16	2032-010C 107.94	12	0	202
1-1/4	2012-012C 155.15	2022-012C 172.41	2032-012C 189.65	6	0	202
1-1/2	2012-015C 169.59	2022-015C 188.96	2032-015C 207.86	6	0	202
2	2012-020C 196.20	2022-020C 217.96	2032-020C 239.76	6	0	202
2-1/2	2012-025C 730.57	2022-025C 788.36	2032-025C 856.05	1	0	203
3	2012-030C 980.92	2022-030C 1089.61	2032-030C 1210.69	1	0	203
4	2012-040C 1765.62	2022-040C 1961.77	2032-040C 2179.75	1	0	203

Flanged Ends

1/2	2013-005C 333.93	2023-005C 370.98	2033-005C 408.04	4	0	202
3/4	2013-007C 361.02	2023-007C 401.08	2033-007C 441.21	4	0	202
1	2013-010C 395.64	2023-010C 439.69	2033-010C 483.64	4	0	202
1-1/4	2013-012C 535.11	2023-012C 594.81	2033-012C 654.29	3	0	202
1-1/2	2013-015C 584.46	2023-015C 651.94	2033-015C 717.04	3	0	202
2	2013-020C 676.81	2023-020C 751.99	2033-020C 827.21	2	0	202
2-1/2	2013-025C 884.28	2023-025C 1168.57	2033-025C 1310.92	1	0	203
3	2013-030C 1226.12	2023-030C 1362.36	2033-030C 1513.75	1	0	203
4	2013-040C 2207.02	2023-040C 2452.24	2033-040C 2724.73	1	0	203



Pressure Rating @ 73°F (23°C), Water
1/2" - 2" 235 psi
Flanged 150 psi

Maximum Service Temperature

PVC = 140°F (60°C)
CPVC = 200°F (93°C)

Temperature/Pressure De-ratings Apply

Plug-Style PE Wedge on All Valves
Rated for Vacuum Service

All Valves Assembled with Silicone-Free,
Water Soluble Lubricants

PVC Socket Ends

Size	Buna-N	EPDM	FKM	Std Pk	Mstr Pk	Prod Code
1/2	5212-005 25.46	5222-005 27.95	5232-005 30.78	12	0	200
3/4	5212-007 31.14	5222-007 34.27	5232-007 36.07	12	0	200
1	5212-010 36.91	5222-010 40.64	5232-010 44.75	12	0	200
1-1/4	5212-012 51.03	5222-012 56.16	5232-012 61.74	6	0	200
1-1/2	5212-015 65.12	5222-015 72.35	5232-015 78.78	6	0	200
2	5212-020 83.63	5222-020 92.07	5232-020 101.22	6	0	200

PVC SR Threaded Ends

Size	Buna-N	EPDM	FKM	Std Pk	Mstr Pk	Prod Code
1/2	5211-005SR 28.34	5221-005SR 30.85	5231-005SR 33.63	12	0	200
3/4	5211-007SR 35.29	5221-007SR 38.43	5231-007SR 40.23	12	0	200
1	5211-010SR 42.64	5221-010SR 46.38	5231-010SR 50.46	12	0	200